

MARPOL® Homo 13.F

Marco Polo International, LLC - Polypropylene Homopolymer

Monday, December 4, 2023

MARPOL® Homo 13.F is formulated to resist gas fading. This resin features excellent processability and good physical properties for fibers and multifilaments.

Recommended Applications Staple fibers and bulk continuous filament

Processing

Product Description

Extrusion, Injection Molding

Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	 Europe Latin America	North America
Features	Excellent Processability	Gas-fading Resistant	 Homopolymer
Uses	BCF Yarn	• Filaments	Staple Fibers
Processing Method	Extrusion	 Injection Molding 	

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Density	0.905	g/cm ³	ASTM D1505		
Melt Mass-Flow Rate (190°C/2.16 kg)	13	g/10 min	ASTM D1238		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Elongation (Yield)	70	%	ASTM D638		
Thermal	Nominal Value	Unit			
Melting Temperature	166	°C			
Additional Information	Nominal Value	Unit	Test Method		
Tenacity	3.50	g/denier	ASTM D3218		

Notes

¹ Typical properties: these are not to be construed as specifications.

